



# BERKELEY® VT SERIES FAIRBANKS NIJHUIS® (LAYNE & BOWLER, VERTI-LINE) IMPELLER INFORMATION AGRICULTURAL MARKET

FLOW SERIES FAIRBANKS NIJHUIS / BERKELEY	FLOW SERIES LAYNE & BOWLER / VERTILINE	IMPELLER PART NUMBER (NO WEAR RING)	VANE TIP WIDTH (IN)	FULL DIAMETER (IN)	ANGLE (DEGREE)
6A	6DRELC	LV4455023 2660F	3/16	4.40	12.50°
6B	6DRMC	LV4455024 2660F	3/16	4.44	9.50°
6D	6RKLC	LV4455025 2660F	1/4	4.62	20.00°
6F	6RKHC	LV4455026 2660F	3/16	4.40	20.00°
6G	6GM	LV4455018 2660F	1/16	4.40	23.00°
6J	6GH	LV4455019 2660F	1/16	4.40	23.00°
7A	7CL	LV4455083 2660F	1/16	5.50	25.00°
7D	7CM	LV4455082 2660F	1/16	5.50	25.00°
7B	7CEH	LV4455084 2660F	1/16	5.50	25.00°
8B	8URHC	LV4455110 1140F	5/16	6.00	16.75°
8P	8RL	LV44550549 2660F	1/16	5.97	25.00°
8T	8RM	LV44550550 2660F	1/16	5.97	25.00°
8V	8RH	LV44550551 2660F	1/16	5.97	25.00°
8U	8TM	LV4455124 2660F	5/16	6.34	33.00°
8W	8TH	LV4455125 2660F	5/16	6.34	33.00°
10VT-250		M16080	1/16	7.692	25.00°
10VT-300		M16081	1/16	7.70	26.00°
10VT275 (closed)		M17139	1/16	7.77	25.30°
10VT400 (closed)		M17058	1/16	8.00	35.00°
10VT550 (closed)		M16734	1/16	8.00	35.00°
10VT700 (closed)		M16735	3/32	8.00	35.00°
10VT900 (closed)		M17148	3/32	8.00	39.90°
10VT1150 (closed)		M16737	1/16	8.00	50.10°
10VT1500 (closed)		M16738	3/32	8.00	29.30°
10VT275 (semi-open)		M17140	1/16	7.77	25.30°
10VT400 (semi-open)		M17059	1/16	8.00	35.00°
10VT550 (semi-open)		M16744	1/16	8.00	35.00°
10VT700 (semi-open)		M16745	3/32	8.00	35.00°
10VT900 (semi-open)		M17149	3/32	8.00	39.90°
10VT1150 (semi-open)		M16747	1/16	8.00	50.10°
10VT1500 (semi-open)		M16748	3/32	8.00	29.30°
10A	10RKLC	LV4455274 2660F	5/16	7.62	21.50°
10B	10RKHC	LV4455275 2660F	1/4	7.62	17.00°
10D	10RKEH	LV4455276 2660F	1/8	7.68	20.50°
10G	10TLC	LV4455277 2660F	1/8	7.96	28.00°
10J	10THC	LV4455278 2660F	1/8	7.96	23.50°
10K	10FHM	LV4450402 2660F	1/8	8.00	40.00
10N	10FHH	LV4450403 2660F	1/8	8.00	40.00°

# BERKELEY® VT SERIES FAIRBANKS NIJHUIS® (LAYNE & BOWLER, VERTI-LINE) IMPELLER INFORMATION AGRICULTURAL MARKET

FLOW SERIES FAIRBANKS NIJHUIS / BERKELEY	FLOW SERIES LAYNE & BOWLER / VERTILINE	IMPELLER PART NUMBER (NO WEAR RING)	VANE TIP WIDTH (IN)	FULL DIAMETER (IN)	ANGLE (DEGREE)
12VT-500		M16086	1/8	9.32	26.00°
12VT-600		M16087	1/8	9.32	26.00°
12VT550 (closed)		M16457	3/16	10.00	26.00°
12VT650 (closed)		M16458	3/16	10.00	26.00°
12VT900 (closed)		M16459	3/16	10.00	37.50°
12VT1100 (closed)		M16461	3/16	10.00	26.00°
12VT1350 (closed)		M16462	3/16	10.00	42.00°
12VT1650 (closed)		M16463	3/16	10.00	32.70°
12VT2000 (closed)		M16464	3/16	10.00	30.00°
12VT2500 (closed)		M16465	3/16	10.00	32.00°
12VT550 (semi-open)		M16467	3/16	10.00	26.00°
12VT650 (semi-open)		M16468	3/16	10.00	26.00°
12VT900 (semi-open)		M16469	3/16	10.00	37.50°
12VT1100 (semi-open)		M16471	3/16	10.00	26.00°
12VT1350 (semi-open)		M16472	3/16	10.00	42.00°
12VT1650 (semi-open)		M16473	3/16	10.00	32.70°
12VT2000 (semi-open)		M16474	3/16	10.00	30.00°
12VT2500 (semi-open)		M16475	3/16	10.00	32.00°
12A	12RKBL	LV4455418 2660F	3/16	9.18	13.50°
12B	12RKBM	LV4455419 2660F	3/16	9.18	13.50°
12D	12RKBH	LV4455420 2660F	3/16	9.18	13.50°
12F	12RKBEH	LV4455428 2660F	3/16	9.18	13.50°
12K	12TLC	LV4455421 2660F	1/16	10.00	30.50°
12S	12THC	LV4455422 2660F	1/16	10.00	30.50°
12E	12RL	LV4455436 2660F	1/16	9.19	25.00°
12G	12RM	LV4455437 2660F	1/16	9.19	25.00°
12I	12RH	LV4455438 2660F	1/16	9.19	25.00°
12N	12FHL	LV4455440 1140F	1/8	9.47	27.50°
12U	12FHM	LV4455441 2660F	1/8	9.47	27.50°
12V	12DEH	LV4455429 2660F	1/4	9.68	30.00°
13E	13CL	LV4455585 2660F	3/32	10.04	25.00°
13F	13CM	LV4455586 2660F	3/32	10.04	25.00°
14C	14RL	LV4450025 1140F	1/8	11.50	31.00°
14F	14RM	LV4450026 2660F	1/8	11.50	31.00°
14D	14RH	LV4450027 2660F	1/8	11.50	31.00°
14I	14FHM	LV4450076 1140F	1/8	11.25	35.00°
14J	14FHH	LV4450077 2660F	1/8	11.25	35.00°
16E	16GM	LV4455732 2660F	1/8	12.78	27.00°

5661 NORTH GOLDEN STATE BLVD., FRESNO, CA 93725-1300  
PH: 559-266-0516 ORDERS FAX: 559-266-5341  
www.BerkeleyPumps.com

3601 FAIRBANKS AVENUE, KANSAS CITY, KANSAS 66106  
PH: 913-371-5000 ORDERS FAX: 913-748-4025  
www.FairbanksNijhuis.com

Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.